

Characteristics of SiPM Photo Sensors for GlueX

E. S. Smith^(a), Y. Qiang^(a), I. Tolstukhin^(a)
W.K. Brooks^(b), H. Hakobyan^(b), S. Kuleshov^(b), O. Soto^(b), A. Toro^(b)
G. Lolo^(c), Z. Papandreou^(c), A. Semenov^(c)

^(a) Jefferson Lab, Newport News, VA 23606 USA

^(b) Universidad Técnica Federico Santa María, Valparaíso, Chile

^(c) University of Regina, Regina, Canada

The barrel calorimeter of the GlueX detector in Hall D at Jefferson Lab will be instrumented with 3840 large-area ($1.2 \times 1.2 \text{ cm}^2$) custom silicon photomultiplier (SiPM) arrays manufactured by Hamamatsu Corporation [1]. These photon sensors have properties similar to vacuum photomultipliers, but are unaffected by high magnetic fields. In our experiment, they will operate in magnetic fields exceeding 1 T. Series of measurements have been carried out by several groups to characterize these SiPMs including the photon detection efficiency (PDE), gain, dark rate, cross talk and after pulsing at different bias voltages and temperatures. A special study was also performed to separate the cross talk and after pulsing by using ADC spectra for the first time. And the time constants of after pulsing were extracted as well. We will present a summary of these measurements and the plan for use of these sensors in the GlueX experiment.

[1] F. Barbosa *et al.*, NIM A695 (2012) 100.

E-mail:

yqiang@jlab.org