# Monte Carlo Simulation of the PRad Experiment at JLab<sup>1</sup>

Li Ye Mississippi State University for the PRad collaboration

<sup>1</sup>.This work is supported in part by NSF MRI award PHY-1229153, the U.S. Department of Energy under Contacts No. DE-FG02-07ER41528, Thomas Jefferson National Laboratory, Mississippi State University and PRad collaboration



# Outline

- PRad Physics goals
- Experimental setup
- Monte-Carlo Simulation
- GEANT4 geometry and beam profile
- Background study and subtraction
- Summary

# The Proton Charge Radius Puzzle

Existing data : 1.electron-proton elastic scattering measurements 2.lamb shift measurements in atomic hydrogen 3.lamb shift measurements in muonic hydrogen



- Muonic hydrogen Lamb shift experiment at PSI (2010,2013)
- r<sub>p</sub> = 0.84184(67) fm Unprecedented less than 0.1% precision
- ~ 7.9 σ discrepancy from most of previous experimental results and analyses

### The PRad Experiment (E12-11-106) The experiment completed data taking during May-June 2016

- Experimental goals:
  - reach very low Q<sup>2</sup> range (~ 10 times less than the Mainz experiment)
  - reach sub-percent precision in r<sub>p</sub> extraction
- Novel Techniques Used:
  - Non-magnetic-spectrometer method: use high resolution high acceptance calorimeter and high position resolution GEM detector
    - reach smaller scattering angles: ( $\Theta = 0.8^{\circ} 7.0^{\circ}$ ) (Q<sup>2</sup> = 2x10<sup>-4</sup> - 1x10<sup>-1</sup>) GeV/c<sup>2</sup> essentially, model independent r<sub>p</sub> extraction
  - 2) Simultaneous detection of  $ee \rightarrow ee$  Moller scattering
    - (best known control of systematics)
  - 3) Use high density windowless H2 gas flow target:
    - beam background fully under control with high quality CEBAF beam
    - minimize experimental background
  - Two beam energies:  $E_0 = 1.1 \text{ GeV}$  and 2.2 GeV to increase Q<sup>2</sup> range: (2x10<sup>-4</sup> 1x10<sup>-1</sup>) GeV/c<sup>2</sup>
  - Will reach sub-percent precision in r<sub>p</sub> extraction





### PRad Experimental Setup (schematics)

More details at WeiZhi Xiong's talk in the same section



- High resolution, Hybrid calorimeter (Magnetic Spectrometer Free)
- Windowless, high density H2 gas flow target (Reduced backgrounds)
- Simultaneous detection of elastic and Moller electrons (control of systematics)
- Vacuum box, one thin window, large area GEM chambers (improved resolution)
- Q<sup>2</sup> range of  $10^{-4} 6 \times 10^{-2}$  GeV<sup>2</sup> (lower than all previous electron scattering expts.)

# Monte-Carlo Simulation

- A thorough simulation of the experiment to identify possible sources of background is important to achieve sub-percent precision in the cross section measurement and proton radius extraction.
- A simulation code for the target and the calorimeter was developed based on GEANT4
- Event generators with radiative corrections of e-p and e-e scattering were also developed.

# GEANT4 geometry and beam profile

#### • Target, made of Kapton

- Cylindricaltube open at both ends and a gas inlet neck

#### • Calorimeter, central part of HyCaL

- 34×34 PbWO<sub>4</sub> crystal modules with four removed at the center
- Dimension of each module: 2.05×2.05×18cm<sup>3</sup>
- Energy resolution 2.6%/ $\sqrt{E}$ , position resolution 2.5mm/ $\sqrt{E}$

#### • Electron beam, 15days of beam time

- 1.1 GeV, 2.2 GeV or higher energy
- A uniform halo of 10<sup>-7</sup> relative to the peak was included.





DNP meeting, vancouver, Oct. 2016

# **GEANT4 Simulation Geometry**

Flange(window Coupling) : material Al, outer diameter 2.3", inner diameter 1.3",

Adapter: material Fe, outer diameter 1.62", inner diameter 1.245",

Quick Disconnect big: material Fe, outer diameter 2", inner diameter 1.39",

Quick Disconnect small: material Fe, outer diameter 1.62", inner diameter 1.39",

#### Beam Pipe:

material Fe, outer diameter 1.375", inner diameter 1.245", note: the beam pipe is all the way connect to the Adapter in the simulation





# Background from Beam Flange



### Background from Beamline and Flange



### Backgrounds From the Beamline Flange



 Background from rescattered Moller events concentrated in first angle bin, around ~2.1% of data.

- Background events as a function of distance from flange to HyCal PbWO<sub>4</sub> surface.
- Total backgrounds on HyCal ~120Hz

## Background from GEMs





Total background in experiment: (HyCal trigger) ~200Hz @ 1.1GeV no target ~350Hz @ 1.1GeV empty target cell and chamber ~550Hz @ 2.2GeV empty target cell and chamber higher than simulation due to residual gas from upstream beamline

Material: G10, Kapton foils, copper, Ar, CO2 ~~0.5% radiation length G10 Frame : 1.5cm ~~7.5% radiation length Distance from Hycal surface : 30cm

# Summary

- The primary background source is from the residual gas and beamline, empty target subtraction will help reduce the background.
- A larger Q<sup>2</sup> coverage is helpful to the radius extraction in this experiment, the expected uncertainty of the extracted radius is less than 1%.
- Radiative corrections are implemented in the simulation.
- Background simulation study helped to make better design of vacuum box window, connection flange and pipe.

